



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number : 0 520 930 A1

(12)

EUROPEAN PATENT APPLICATION

(21) Application number : 92500067.1

(51) Int. Cl.⁵ : A61M 5/32

(22) Date of filing : 29.05.92

(30) Priority : 30.05.91 ES 9101712 U

(43) Date of publication of application :
30.12.92 Bulletin 92/53

(84) Designated Contracting States :
AT BE CH DE DK FR GB GR IT LI LU MC NL PT
SE

(71) Applicant : SERRANO GONZALEZ, Antonio
Riu Canyoles 6
E-46900 El Vedat de Torrent (Valencia) (ES)

(72) Inventor : SERRANO GONZALEZ, Antonio
Riu Canyoles 6
E-46900 El Vedat de Torrent (Valencia) (ES)

(74) Representative : Garcia Cabrerizo, Francisco
OFICINA GARCIA CABRERIZO S.L. Vitrivio 23
E-28006 Madrid (ES)

(54) Protector for self-retractile hypodermic needles.

(57) A protector for self-retractile hypodermic needles, the purpose of which is to hide and protect the needle used in injections, both before and after its use. Its basic features are a tubular body (1) opened on both ends and cylindrical, at least inside, including an inner ring-shaped projection (3) with minimum width and thickness, which holds the needle-holder (6). The body includes as well an expansion spring (5) placed between the end projection of the needle-holder provided to be held against the inner projection of the tubular body, and the strangled front end of the latter. The spring pushes the needle-holder in, hiding the needle (7), once the syringe has been used for an injection. The tubular body is provided with elongated side windows (4) to simultaneously hold both the tubular body and the syringe during use.




Fig. 1

EP 0 520 930 A1

This invention consists of a protector for self-retractile hypodermic needles. It aims at providing the market and general public with a new item which prevents any contact with the hypodermic needle, both before and after use, as well as preventing any accidental pricks with syringes left lying on the ground.

This protector is designed to optionally have a built-in needle-holder with its needle. It has an inner cylindrical and hollow form, with elongated side windows and a small ring-shaped inner projection — placed in front of its middle length. The width of this projection is small and it acts as an anchorage for the needle-holder, which is kept in place by means of a complementary groove on its back end, that is, the end opposite the one where the needle is emerging. It is provided as well with an inner expansion spring situated between the afore mentioned ring-shaped projection and the front end of the cylindrical body.

Anchorage for the needle-holder over this projection of the protector is such that a minimum push is enough to free it, thus moving the needle-holder and allowing the needle to emerge at the required moment, to be immediately pushed back by the action of the afore mentioned expansion spring. In addition to the described functions, the protector obviously allows the corresponding syringe to be inserted. This will move axially along the protector until its end is fitted on to the needle-holder. At this moment, if one continues to push, the needle-holder will disengage itself, as previously explained, and will move outwards. Then the needle will emerge ready for use, first to suction the medicine through its piston and then to inject it. Once this operation is completed, the syringe is pulled back, the needle-holder being also pushed back by the spring and concealing the needle in the process.

The purpose of the elongated side windows with which the protector is provided is to be able to hold at the same time both protector and syringe whenever the syringe is inside.

For a better understanding of the features of this invention, here follows a detailed description referring to the sheet of drawings attached as an integral part of this description, for guidance only. The following items are shown in the said figures:

Figure 1 shows a longitudinal section of the protector together with the retracted needle-holder and the hidden needle.

Figure 2 shows a longitudinal section of the same protector with the needle-holder pushed back and the emerging needle.

Figure 3 shows the hidden position of the needle and needle-holder after use.

Numbers in these figures refer to the following parts:

- 1.- Protector body.
- 2.- Strangled end of the body. (1)
- 3.- Inner ring-shaped projection of the body (1).

4.- Side windows of the body. (1)

5.- Expansion spring.

6.- Needle-holder.

7.- Needle.

8.- End projection of the needle-holder (6).

As can be seen in these figures, the protector herein described consists of a cylindrical body (1), hollow and opened at both ends, with the end regarded as front end showing a narrowing (2).

This body (1) of the protector shows inside a ring-shaped projection (3) of minimum thickness and small width, which is placed a little ahead of its medium length. The backward portion from the projection area (3) shows some elongated windows (4). An expansion spring (5) is placed inside, between the ring-shaped projection (3) and the narrowed or strangled end (2).

The protector thus formed can be marketed in this configuration or with a built-in needle-holder (6) and the needle itself (7). The needle-holder (6) includes in its back end a ring-shaped projection (8) to hold it against the ring-shaped projection (3) of the protector, so that the needle-holder (6) will be held in this position with the needle (7) completely hidden and protected, as shown in Figure 1.

When using it, the injection syringe will be axially inserted through the back end of the protector (1), until fitting on to the end mouthpiece of the said syringe in the needle-holder (6). Then, if the syringe continues to be pushed, the projection (8) of the needle-holder (6) will go beyond the projection (3) of the protector, both the former and the needle (7) being pushed until the needle emerges, as shown in Figure 2, overcoming the spring resistance (5).

In this position the medicine to be injected can be suctioned through the syringe piston. This operation is possible without the syringe or the needle-holder (6) moving backwards, since the user will be holding the syringe through the windows (4) whilst holding the protector (1).

Once the medicine has been injected, the syringe is pushed back and drawn from the protector. At the same time, the spring (5) will cause the needle-holder (6) to retract and therefore the needle (7) to hide again, the needle-holder (6) being held when its end projection (8) is fitted on to the lower step of the projection (3) belonging to the protector.

Claims

1st.- A protector for self-retractile hypodermic needles, the purpose of which is to hide and protect the needle used in injections, both before and after its use. Its basic features are a tubular body opened on both ends and cylindrical, at least inside, including an inner ring-shaped projection with minimum width and thickness, which holds the needle-holder. The body includes as well an expansion spring placed between

the end projection of the needle-holder provided to be held against the inner projection of the tubular body, and the strangled front end of the latter. The spring pushes the needle-holder in, hiding the needle, once the syringe has been used for an injection. The tubular body is provided with elongated side windows to simultaneously hold both the tubular body and the syringe during use.

5

10

15

20

25

30

35


40

45

50

55

3





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 92 50 0067

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 8)
X	US-A-3 305 290 (KELTMAN) * column 3, line 2 - line 5; figures *	1	A51F5/32
A	EP-A-0 317 518 (TAKBURINI) * column 2, line 21 - line 26; figures 1,2 *	1	
A	US-A-4 816 022 (POPEY) * abstract; figures *	1	
A	US-A-4 966 592 (BURRS ET AL) * abstract; figures *	1	
A	UD-A-8 904 678 (HABLEY MEDICAL TECHNOLOGY) * abstract; figures *	1	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int. Cl. 8)
			A51H
Place of search THE HAGUE		Date of completion of the search 03 SEPTEMBER 1992	Searcher CLARKSON P.
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons Δ : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (01.92) (P.2/3)